

**MIL-L-10287B
CELLULOSE NITRATE LACQUER**

TECHNICAL DATA SHEET	
DESCRIPTION:	
A cellulose nitrate lacquer used in both the manufacture of small arms ammunition for identification purposes and in the assembly of small arms ammunition primers.	
TYPICAL PROPERTIES:	
COLORS:	All fed Std 595B
TYPE I :	Opaque
TYPE II :	Semi- Transparent
DRYING TIME:	Within 4 minutes
SOLIDS (weight)	30-35 %
APPLICATION & REDUCTION:	
May be applied by brush, roll, spray or dip tank application. Brush and roll small areas only due to quick drying characteristics. Thin with TT-T-266D up to 1/2 pint per gallon to a viscosity of 40-50% centipoise or as needed for proper application.	
SAFETY:	Distributed by:
<p>READ MATERIAL SAFETY DATA SHEETS BEFORE USING THIS PRODUCT.</p> <p>Contents are Flammable</p> <p>Keep away from heat and open flames</p> <p>For Industrial Use Only</p> <p>Avoid Breathing Vapor or Mist</p>	<p>PACIFIC RESINS & COATINGS LTD. 151- 5489 Byrne Road, Burnaby, B.C., Canada, V5J-3J1 Phone 604-432-6111 Fax 604-432-7006 Website: pwpaints.com Email info@pwpaints.com</p> <p>Specializing in MIL-SPEC Coatings.</p>