

# TT-E-529G SEMIGLOSS ALKYD ENAMEL

<b>TECHNICAL DATA SHEET</b>	
<b>DESCRIPTION:</b>	
TT-P-529G is a semi-gloss, alkyd enamel formulated for interior and exterior metal and wood surfaces. This coating is primarily used as a medium dry finish coat on equipment.	
<b>PROPERTIES:</b>	
<b>COLORS:</b> full range	Fed Std 595b
<b>GRIND</b>	Not under 6
<b>Specular Gloss</b>	15-25 @ 60 Deg.
<b>Viscosity</b>	67-77 KU
<b>Dry Times @77 °F</b>	To Touch 2hrs. * Dry Hard 8 hrs. * Full Hard 72 hrs. *
* times will vary with humidity, temperature and film thickness.	
<b>Thinner</b>	Xylene
<b>Shelf Life @ 77 °F</b>	12 months ( D.M.)
<b>ADVANTAGES:</b>	
Interior/Exterior use Semi-Gloss Finish Meets TT-E-529G Fast Production Time	
<b>USES:</b>	
Steel / Wood Machinery Tanks Towers	
<b>SAFETY:</b>	
Refer to <b>Material Safety Data Sheets</b> before use FOR PROFFESIONAL USE ONLY CONTENTS ARE FLAMMABLE AVOID BREATHING MIST OR VAPOR	
<b>PRIMERS</b>	
STEEL:	TT-P-664D
ALUMINUM:	MIL-C-8514C (1st) MTT-P-664D (2nd)
<b>Distributed by:</b>	
<b>PACIFIC RESINS &amp; COATINGS LTD.</b> AIRCRAFT COATINGS & RESINS 151- 5489 Byrne Road, Burnaby,BC, Canada, V5J 3J1 Phone (604)432-6111 or (604)430-4151 Fax (604)432-7006 e-mail info@pwpaints.com Web Site: www.pwpaints.com	
<b>APPLICATION:</b>	
TT-E-529G Enamels can be applied by conventional or airless spray application. For spray application thin up to 10% or as needed with zylene. For brushing use as is or with minimum thinning.	